



Specifications

Model		RCM3A	RCM5A	RCM8A	RCM10A	RCM12A	RCM15A	RCM20A	RCM25A	RCM30A
chilling capacity	KW	7.5	12.5	18	23	28	36	46	58	72
	KCAL/H	6450	10750	15480	19780	24080	30960	39560	49880	61920
Compressor outputpower		Scroll compressor								
Compressor outputpower	HP	3	5	8	10	12	15	20	25	30
Refrigerant		R22/R407C								
Refrigerant Filling quantity	KG	2	3	5	6	7.5	10	12	15	20
Pump power	KW	0.75	0.75	0.75	1.5	1.5	2.2	2.2	2.2	2.2
pump max flowrate	L/MIN	100	100	100	200	200	600	600	600	600
Pipe size outlet	INCH	1	1	1	1.5	1.5	1.5	2.5	2.5	2.5
Pipe size outlet	INCH	1	1	1	1.5	1.5	1.5	2.5	2.5	2.5
Blower power	KW	0.25	0.19x2	0.25x2	0.42x2	0.25x4	0.25x4	0.42x4	0.42x6	0.42x6
Tank capacity	L	56	65	113	129	173	173	271	350	400
(L)	mm	1090	1250	1350	1350	1700	1700	1900	2150	2150
(W)	mm	760	760	860	960	1200	1200	1200	1480	1480
(H)	mm	1250	1320	1560	1620	1750	1750	1750	1800	1800

Note:

1) The cooling capacity is measured when the outgoing water temperature is 7°C and ambient temperature is 30°C.